




See nothing, hear everything

The CWM7.5 shares the acoustic configuration of the 707 S2 and like its sibling, it houses a 130mm (5in) bass/mid-range Continuum cone driver plus a 25mm (1in) Carbon Dome tweeter, coupled to a forward-firing Flowport™ for outstanding bass response from a relatively small footprint. It has a critically formed baffle constructed from glass reinforced ABS plus its own integrated backbox, ensuring retrofittable installation plus optimum performance. It's an outstanding performer when used in stereo or multi-room installations, and is equally at home as the rear speaker in a larger theatre application.

Technical Specifications	
Technical features	Carbon Dome tweeter Continuum mid/bass Flowport™
Description	2-way in-wall system
Drive units	1x ø25mm (1 in) Carbon Dome high-frequency 1x ø130mm (5 in) Continuum cone mid/bass
Frequency range (-6dB)	-6dB at 43Hz and 33kHz
Frequency Response -3dB	45Hz - 28kHz ±3dB
Sensitivity	86dB spl (2.83Vrms, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 90Hz - 33kHz <0.5% 120Hz - 33kHz
Nominal impedance	8Ω (minimum 3.8Ω)
Recommended amplifier power	25W - 150W into 8Ω on unclipped programme
Frame height	356mm (14in)
Frame width	212mm (8.5in)
Depth (behind surface)	102mm (4in)
Cut-out height	331mm (13in)
Cut-out width	187mm (7.4in)
Cut-out height w/PMK	336mm (13.2in)
Cut-out width w/PMK	192mm (7.6in)
Reservoir box height	385mm (15.2in)
Reservoir box width	181mm (7.1in)
Protrusion	8mm (0.32in)
PMK	7.5W
Net weight	3.8kg (8.38 lb)
Finishes	Back box: White Grille: White