



Bowers & Wilkins

HTM72 S3

Technical Information



Technical features

Decoupled Carbon Dome tweeter
Continuum™ cone bass / midrange
Flowport™

Description

2-way vented-box system

Drive units

1x ø25mm (1in) Decoupled Carbon Dome high-frequency
2x ø130mm (5in) Continuum cone bass / midrange

Frequency range

48Hz to 33kHz

Frequency response

(+/-3dB from reference axis)

70Hz - 28kHz

Sensitivity

(on axis at 2.83Vrms at 1m)

87dB

Harmonic distortion

2nd and 3rd harmonics (90dB, 1m on axis)

<1% 100Hz - 22kHz

<0.5% 200Hz - 22kHz

Nominal impedance

8Ω (minimum 4.3Ω)

Recommended amplifier power

30W - 120W into 8Ω on unclipped programme

Max. recommended cable impedance

0.1Ω

Dimensions

Height: 165mm (6.5in) cabinet only

Width: 477mm (18.8in) cabinet only

Depth: 266mm (10.5in) cabinet only

302mm (11.9in) including grille and terminals

Net weight

9.7kg (21.3lbs)

Finishes

Cabinet: Gloss black
Satin white
Mocha
Rosenut (APAC only)

Grille: Black
Grey (Satin White only)